

SIDING  
PRODUCT  
DIRECTORY

VINYL AND METAL



Siding • Soffit • Accessories



# GENTEK PRODUCT DIRECTORY


	<u><b>INSULATED VINYL SIDING</b></u>
4	SEQUOIA SELECT ENFUSION <b>NEW!</b>
	<u><b>VINYL SIDING</b></u>
5	SEQUOIA SELECT
6	SEQUOIA SELECT BOARD & BATTEN
7	SEQUOIA SELECT VARIEGATED
8	SEQUOIA SELECT EXTENDED LENGTH
9-10	SIGNATURE SUPREME
11	BERKSHIRE BEADED & CENTENNIAL BEADED
12-13	CONCORD/ADVANTAGE III
14	AURORA
	<u><b>SHAKES &amp; SCALLOPS</b></u>
15-16	FAIRHAVEN SOUND SINGLE SELECT
	<u><b>VINYL SOFFIT &amp; ACCESSORIES</b></u>
17	SEQUOIA SELECT Ultra-Premium Soffit
18	OXFORD Premium Soffit
19	BEADED Premium Soffit
20	FAIRWEATHER Soffit
21	Deep-Pocket Insulated Vinyl Accessories
22-31	Vinyl Accessories
	<u><b>ALUMINUM SIDING</b></u>
32	CEDARWOOD & WOODGRAIN SERIES 2000
33	DELUXE
	<u><b>ALUMINUM SOFFIT, FASCIA &amp; ACCESSORIES</b></u>
34-35	HI-TENSILE Soffit – LoMar Poly Finish
36	PVC SUPREME Soffit – PVC Finish
37	VALUGARD Soffit
38	DELUXE Fascia
39	VALUGARD Fascia
40-43	Aluminum Accessories
	<u><b>STEEL SIDING</b></u>
44	STEELTEK
45	STEELSIDE
46	DRIFTWOOD
47	UNIVERSAL
	<u><b>STEEL FASCIA &amp; ACCESSORIES</b></u>
48	Steel Fascia
49-51	Steel Accessories
	<u><b>TRIM COIL</b></u>
52-54	Aluminum Trim Coil
55	Steel Trim Coil
	<u><b>GUTTER COIL</b></u>
56-57	Aluminum Gutter Coil
	<u><b>COLOR MATRIX</b></u>
58-59	Vinyl Siding
60-61	Shakes & Scallops
60-61	Vinyl Soffit
62-63	Deep-Pocket Insulated Vinyl Accessories
64-65	Vinyl Accessories
66-67	Aluminum Siding, Soffit & Fascia
68-69	Aluminum Accessories
70-71	Steel Siding & Fascia
72-73	Steel Accessories
74-75	Aluminum & Steel Trim Coil
76-77	Trim Coil – Competitive Brands
78-79	Gutter Coil
	<u><b>ARCHITECTURAL SPECIFICATIONS</b></u>
80-81	Vinyl Architectural Specifications
82-83	Shakes & Scallops Architectural Specifications
84-85	Aluminum Architectural Specifications
86-87	Steel Architectural Specifications

**PRODUCT CODE & DESCRIPTION**

**13570**  
**Double 5"**  
**Dutch Lap**

3/4" Butt (19)  
 Panel Projection 1-1/4" with foam  
 2-5" Exposure per Panel (127/254)  
 16'4" Lengths (4979)  
 .046" Nominal Thickness  
 Cedargrain Texture


Packaging:  
 7 pcs. per ctn.  
 .95 sq. per ctn. (8.84 m<sup>2</sup>)  
 Ship. wt: 56.8 lb (25.8 kg)



**13575**  
**Double 6"**

3/4" Butt (19)  
 Panel Projection 1-1/4" with foam  
 2-6" Exposure per Panel  
 (152.4/304.8)  
 16'8" Lengths (5080)  
 .046" Nominal Thickness  
 Cedargrain Texture

Packaging:  
 6 pcs. per ctn.  
 1 sq. per ctn. (9.3 m<sup>2</sup>)  
 Ship. wt: 55.7 lb (25.3 kg)



For deep-pocket insulated vinyl siding accessories, see page 21.

**COLORS**


- Snow White
- Almond
- Antique Ivory
- Dover Gray
- Canyon Clay
- Pebble
- Sage
- Wicker
- Dark Drift
- Harvest Wheat
- Midnight Surf
- Moonlit Moss
- Saddle Brown
- Venetian Red
- Windswept Smoke

**PRODUCT CODE & DESCRIPTION**

**13715**  
**Double 4"**

3/4" Butt (19)  
 2-4" Exposure per Panel  
 (101.6/203.2)  
 12'6" Lengths (3810)  
 .046" Nominal Thickness  
 Cedargrain Texture


Packaging:  
 24 pcs. per ctn.  
 2 sqs. per ctn. (18.6 m<sup>2</sup>)  
 Ship. wt: 112 lb (50.8 kg)



**13714**  
**Double 4-1/2"**  
**Dutch Lap**

3/4" Butt (19)  
 2-4.5" Exposure per Panel  
 (114.5/229)  
 12'1" Lengths (3683)  
 .046" Nominal Thickness  
 Cedargrain Texture


Packaging:  
 22 pcs. per ctn.  
 2 sqs. per ctn. (18.6 m<sup>2</sup>)  
 Ship. wt: 102.5 lb (46.5 kg)



**13719**  
**Double 5"**

3/4" Butt (19)  
 2-5" Exposure per Panel (127/254)  
 12' Lengths (3658)  
 .046" Nominal Thickness  
 Cedargrain Texture


Packaging:  
 20 pcs. per ctn.  
 2 sqs. per ctn. (18.6 m<sup>2</sup>)  
 Ship. wt: 100 lb (45 kg)



**13741**  
**Double 5"**  
**Dutch Lap**

3/4" Butt (19)  
 2-5" Exposure per Panel (127/254)  
 12' Lengths (3658)  
 .046" Nominal Thickness  
 Cedargrain Texture

Packaging:  
 20 pcs. per ctn.  
 2 sqs. per ctn. (18.6 m<sup>2</sup>)  
 Ship. wt: 102.5 lb (46.5 kg)




**COLORS**

- Snow White
- Almond
- Antique Ivory
- Dover Gray
- Linen
- Maize
- Mist Blue
- Pearl
- Sandalwood
- Sandstone
- Canyon Clay
- Pebble
- Sage
- Wicker
- Dark Drift
- Harvest Wheat
- Midnight Surf
- Moonlit Moss
- Saddle Brown
- Venetian Red
- Windswept Smoke

**PRODUCT CODE & DESCRIPTION**

13373  
**7" Board & Batten**



1/2" Batten Height (12.7)  
1-1/2" Batten Width (38.1)  
7" Exposure per Panel (178.5)  
10' Lengths (3048)  
.050" Nominal Thickness  
Light Roughsawn Texture


Packaging:  
17 pcs. per ctn.  
1 sq. per ctn. (9.2 m<sup>2</sup>)  
Ship. wt: 50 lb (23 kg)

**COLORS**

- Snow White
- Almond
- Antique Ivory
- Dover Gray
- Linen
- Maize
- Mist Blue
- Pearl
- Sandalwood
- Sandstone
- Canyon Clay
- Pebble
- Sage
- Wicker
- Dark Drift
- Harvest Wheat
- Midnight Surf
- Moonlit Moss
- Saddle Brown
- Venetian Red
- Windswept Smoke

**PRODUCT CODE & DESCRIPTION**

13731  
**Double 4"**




3/4" Butt (19)  
2-4" Exposure per Panel (101.6/203.2)  
12'6" Lengths (3810)  
.046" Nominal Thickness  
Cedargrain Texture

Packaging:  
24 pcs. per ctn.  
2 sqs. per ctn. (18.6 m<sup>2</sup>)  
Ship. wt: 112 lb (50.8 kg)

- Aspen
- Chestnut
- Earthen
- Maple
- Rainforest
- Willow


13732  
**Double 5"**



3/4" Butt (19)  
2-5" Exposure per Panel (127/254)  
12' Lengths (3658)  
.046" Nominal Thickness  
Cedargrain Texture

Packaging:  
20 pcs. per ctn.  
2 sqs. per ctn. (18.6 m<sup>2</sup>)  
Ship. wt: 100 lb (45 kg)


13734  
**Double 5" Dutch Lap**



3/4" Butt (19)  
2-5" Exposure per Panel (127/254)  
12' Lengths (3658)  
.046" Nominal Thickness  
Cedargrain Texture

Packaging:  
20 pcs. per ctn.  
2 sqs. per ctn. (18.6 m<sup>2</sup>)  
Ship. wt: 102.5 lb (46.5 kg)

13379  
**7" Board & Batten**



1/2" Batten Height (12.7)  
1-1/2" Batten Width (38.1)  
7" Exposure per Panel (178.5)  
10' Lengths (3048)  
.050" Nominal Thickness  
Light Roughsawn Texture


Packaging:  
17 pcs. per ctn.  
1 sq. per ctn. (9.2 m<sup>2</sup>)  
Ship. wt: 50 lb (23 kg)

**PRODUCT CODE & DESCRIPTION**

**13710**  
**Double 4"**

3/4" Butt (19)  
2-4" Exposure per Panel  
(101.6/203.2)  
16'1" Lengths (4903)  
.046" Nominal Thickness  
Cedargrain Texture

Packaging:  
14 pcs. per ctn.  
1.5 sqs. per ctn. (14 m<sup>2</sup>)  
Ship. wt: 80.4 lb (36.5 kg)




**COLORS**

Snow White  
Antique Ivory  
Almond  
Dover Gray  
Linen  
Maize  
Mist Blue  
Pearl  
Sandalwood

**13742**  
**Double 5"**  
**Dutch Lap**

3/4" Butt (19)  
2-5" Exposure per Panel (127/254)  
16'4" Lengths (4979)  
.046" Nominal Thickness  
Cedargrain Texture




Packaging:  
11 pcs. per ctn.  
1.5 sqs. per ctn. (14 m<sup>2</sup>)  
Ship. wt: 73.2 lb (33.2 kg)

Canyon Clay  
Pebble  
Sage  
Wicker

**13746**  
**Double 4"**


3/4" Butt (19)  
2-4" Exposure per Panel  
(101.6/203.2)  
24'8" Lengths (7518)  
.046" Nominal Thickness  
Cedargrain Texture



Packaging:  
9 pcs. per ctn.  
Approx 1.5 sqs. per ctn. (14 m<sup>2</sup>)  
Ship. wt: 77.2 lb (35 kg)

**13748**  
**Double 5"**  
**Dutch Lap**

3/4" Butt (19)  
2-5" Exposure per Panel (127/254)  
24'8" Lengths (7518)  
.046" Nominal Thickness  
Cedargrain Texture




Packaging:  
7 pcs. per ctn.  
1.65 sqs. per ctn. (15.3 m<sup>2</sup>)  
Ship. wt: 79.5 lb (36 kg)

**PRODUCT CODE & DESCRIPTION**

**13404**  
**Double 4"**

5/8" Butt (15.9)  
2-4" Exposure per Panel  
(101.6/203.2)  
12'6" Lengths (3810)  
.044" Nominal Thickness  
Hardwood Texture


Packaging:  
24 pcs. per ctn.  
2 sqs. per ctn. (18.6 m<sup>2</sup>)  
Ship. wt: 99 lb (45 kg)



Snow White  
Almond  
Antique Ivory  
Dover Gray  
Linen  
Maize  
Mist Blue  
Pearl  
Sandalwood

**13436**  
**Double 4"**  
**Dutch Lap**

5/8" Butt (15.9)  
2-4" Exposure per Panel  
(101.6/203.2)  
12'6" Lengths (3810)  
.044" Nominal Thickness  
Hardwood Texture




Packaging:  
24 pcs. per ctn.  
2 sqs. per ctn. (18.6 m<sup>2</sup>)  
Ship. wt: 99 lb (45 kg)

Canyon Clay  
Pebble  
Sage  
Wicker

**13413**  
**Double 5"**


5/8" Butt (15.9)  
2-5" Exposure per Panel (127/254)  
12' Lengths (3658)  
.044" Nominal Thickness  
Hardwood Texture



Packaging:  
20 pcs. per ctn.  
2 sqs. per ctn. (18.6 m<sup>2</sup>)  
Ship. wt: 91 lb (41 kg)

**13415**  
**Double 5"**  
**Dutch Lap**

5/8" Butt (15.9)  
2-5" Exposure per Panel (127/254)  
12' Lengths (3658)  
.044" Nominal Thickness  
Hardwood Texture



Packaging:  
20 pcs. per ctn.  
2 sqs. per ctn. (18.6 m<sup>2</sup>)  
Ship. wt: 91 lb (41 kg)



# SIGNATURE SUPREME® VINYL SIDING


## PRODUCT CODE & DESCRIPTION

## COLORS

13481  
8"

5/8" Butt (15.9)  
8" Exposure per Panel (203.2)  
12'6" Lengths (3810)  
.044" Nominal Thickness  
Hardwood Texture

Snow White



Packaging:  
24 pcs. per ctn.  
2 sqs. per ctn. (18.6 m<sup>2</sup>)  
Ship. wt: 97 lb (44 kg)

# Berkshire™ VINYL SIDING


## PRODUCT CODE & DESCRIPTION

## COLORS

13639  
6-1/2" Beaded

3/4" Butt (19)  
6-1/2" Exposure per Panel (165.1)  
12'3-3/4" Lengths (3753)  
.046" Nominal Thickness  
Brushed Texture

Snow White



Packaging:  
30 pcs. per ctn.  
2 sqs. per ctn. (18.6 m<sup>2</sup>)  
Ship. wt: 102 lb (46 kg)


Almond  
Antique Ivory  
Dover Gray  
Linen  
Maize  
Mist Blue  
Pearl  
Sandalwood  
Sandstone

Canyon Clay  
Pebble  
Sage  
Wicker

# CENTENNIAL™ VINYL SIDING

13629  
6-1/2" Beaded

11/16" Butt (17.5)  
6-1/2" Exposure per Panel (165.1)  
12'3-3/4" Lengths (3753)  
.046" Nominal Thickness  
Brushed Texture




Packaging:  
30 pcs. per ctn.  
2 sqs. per ctn. (18.6 m<sup>2</sup>)  
Ship. wt: 102 lb (46 kg)



**PRODUCT CODE & DESCRIPTION**

**13904  
Double 4"**




1/2" Butt (12.7)  
2-4" Exposure per Panel  
(101.6/203.2)  
12'6" Lengths (3810)  
.042" Nominal Thickness  
Light Roughsawn Texture

Packaging:  
24 pcs. per ctn.  
2 sqs. per ctn. (18.6 m<sup>2</sup>)  
Ship. wt: 94 lb (43 kg)

**COLORS**

Snow White  
Almond  
Antique Ivory  
Dover Gray  
Linen  
Maize  
Mist Blue  
Pearl  
Sandalwood  
Sandstone

**13912  
Double 4"  
Dutch Lap**




1/2" Butt (12.7)  
2-4" Exposure per Panel  
(101.6/203.2)  
12'6" Lengths (3810)  
.042" Nominal Thickness  
Light Roughsawn Texture

Packaging:  
24 pcs. per ctn.  
2 sqs. per ctn. (18.6 m<sup>2</sup>)  
Ship. wt: 94 lb (43 kg)

Canyon Clay  
Pebble  
Sage  
Storm  
Wicker


**13939  
Double 5"**



1/2" Butt (12.7)  
2-5" Exposure per Panel (127/254)  
12' Lengths (3658)  
.042" Nominal Thickness  
Light Roughsawn Texture

Packaging:  
20 pcs. per ctn.  
2 sqs. per ctn. (18.6 m<sup>2</sup>)  
Ship. wt: 91 lb (41 kg)

**13930  
Double 5"  
Dutch Lap**




1/2" Butt (12.7)  
2-5" Exposure per Panel (127/254)  
12' Lengths (3658)  
.042" Nominal Thickness  
Light Roughsawn Texture

Packaging:  
20 pcs. per ctn.  
2 sqs. per ctn. (18.6 m<sup>2</sup>)  
Ship. wt: 90 lb (41 kg)



**PRODUCT CODE & DESCRIPTION**

**13291  
Triple 3"  
(Advantage III)**



1/2" Butt (12.7)  
3-3" Exposure per Panel  
(76.2/229)  
12'1" Lengths (3683)  
.042" Nominal Thickness  
Brushed Texture

Packaging:  
22 pcs. per ctn.  
2 sqs. per ctn. (18.6 m<sup>2</sup>)  
Ship. wt: 96 lb (44 kg)


**COLORS**

Snow White  
Almond  
Antique Ivory  
Dover Gray  
Linen  
Maize  
Mist Blue  
Pearl  
Sandalwood  
Sandstone  
Canyon Clay  
Pebble  
Sage  
Storm  
Wicker



**PRODUCT CODE & DESCRIPTION**

**13830**  
**Double 4"**  
7/16" Butt (11.1)  
2-4" Exposure per Panel  
(101.6/203.2)  
12'6" Lengths (3810)  
.040" Nominal Thickness  
Driftwood Texture




Packaging:  
24 pcs. per ctn.  
2 sqs. per ctn. (18.6 m<sup>2</sup>)  
Ship. wt: 89 lb (40 kg)

**COLORS**

- Snow White
- Almond
- Antique Ivory
- Dover Gray
- Linen
- Maize
- Pearl
- Sandalwood
- Sandstone

**13820**  
**Double 4-1/2"**  
**Dutch Lap**

7/16" Butt (11.1)  
2-4.5" Exposure per Panel  
(114.5/229)  
12'1" Lengths (3683)  
.040" Nominal Thickness  
Driftwood Texture



Packaging:  
22 pcs. per ctn.  
2 sqs. per ctn. (18.6 m<sup>2</sup>)  
Ship. wt: 85 lb (39 kg)


- Canyon Clay
- Pebble
- Sage
- Wicker



Ultra-Premium Shakes & Scallops

**PRODUCT CODE & DESCRIPTION**

**13988**  
**Traditional Shake**  
5/8" Butt (15.9)  
7" Single Exposure (177.8)  
6'9" Lengths (2057.4)  
.085" Nominal Thickness  
Natural Cedar Texture  
Polypropylene




Packaging:  
13 pcs. per ctn.  
.5 sq. per ctn. (4.65 m<sup>2</sup>)  
Ship. wt: 40 lb (18.1 kg)

- Snow White
- Almond
- Antique Ivory
- Dover Gray
- Linen
- Maize
- Pearl
- Sandstone

**13992**  
**Scallop**

1/2" Butt (12.7)  
6-1/4" Single Exposure (158.8)  
6'4" Lengths (1930.4)  
.085" Nominal Thickness  
Natural Cedar Texture  
Polypropylene




Packaging:  
15 pcs. per ctn.  
.5 sq. per ctn. (4.65 m<sup>2</sup>)  
Ship. wt: 35 lb (15.9 kg)

- Canyon Clay
- Pebble
- Sage
- Wicker

**13994**  
**Cape Cod Shingle**

1/2" Butt (12.7)  
2-5" Exposure per Panel (127/254)  
5'5" Lengths (1651)  
.075" Nominal Thickness  
Natural Cedar Texture  
Polypropylene




Packaging:  
11 pcs. per ctn.  
.5 sq. per ctn. (4.65 m<sup>2</sup>)  
Ship. wt: 35 lb (15.9 kg)

- Dark Drift
- Harvest Wheat
- Midnight Surf
- Moonlit Moss
- Saddle Brown
- Venetian Red
- Windswept Smoke

**13993**  
**Hand-Split Shake**

5/8" Butt (15.9)  
9" Single Exposure (228.6)  
6'4-1/2" Lengths (1943.1)  
.100" Nominal Thickness  
Polypropylene  
Deep Cedargrain Texture  
Staggered Bottom Edge



Packaging:  
11 pcs. per ctn.  
.5 sq. per ctn. (4.65 m<sup>2</sup>)  
Ship. wt: 44 lb (20 kg)




**PRODUCT CODE & DESCRIPTION**

**COLORS**

**14972**  
**Traditional Shake**  
**Corner**

15.86" Lengths (402.8)  
 Natural Cedar Texture

Packaging:  
 10 pcs. per ctn.  
 13.2 lineal ft. per ctn. (4 m)  
 Ship. wt: 7 lb (3.2 kg)



Snow White  
 Almond  
 Antique Ivory  
 Dover Gray  
 Linen  
 Maize  
 Pearl  
 Sandstone

**14974**  
**Hand-Split Shake**  
**Corner**

20.18" Lengths (512.6)  
 Deep Cedargrain Texture

Packaging:  
 10 pcs. per ctn.  
 16.8 lineal ft. per ctn. (5.1 m)  
 Ship. wt: 10.5 lb (4.8 kg)



Canyon Clay  
 Pebble  
 Sage  
 Wicker  
 Dark Drift  
 Harvest Wheat  
 Midnight Surf  
 Moonlit Moss  
 Saddle Brown  
 Venetian Red  
 Windswept Smoke

**15160**  
**Starter Strip\***

10' Lengths (3.1 m)

Packaging:  
 25 pcs. per ctn.  
 250 lineal ft. per ctn. (146.3 m)  
 Ship. wt: 57 lb (25.9 kg)



No Color

\*Aluminum starter strip.

**13998**  
**AccuClip**

Packaging:  
 25 pcs. per bag  
 4 bags per ctn.

Stainless steel install clip secures top  
 course of shake and scallops.




**PRODUCT CODE & DESCRIPTION**

**COLORS**

**16388**  
**12" T-4**  
**Solid Soffit/  
 Vertical Siding**

12" Exposure per Panel (304.8)  
 12' Lengths (3658)  
 .044" Nominal Thickness  
 Matte Texture

Packaging :  
 16 pcs. per ctn.  
 1.92 sqs. per ctn. (17.8 m<sup>2</sup>)  
 Ship. wt: 109.2 lb (49.53 kg)




Snow White  
 Almond  
 Antique Ivory  
 Dover Gray  
 Linen  
 Maize  
 Mist Blue  
 Pearl  
 Sandalwood

**16386**  
**12" T-4**  
**Soffit/Hidden Vent**

12" Exposure per Panel (304.8)  
 12' Lengths (3658)  
 .044" Nominal Thickness  
 Matte Texture  
 10 sq. inches ventilation  
 per lineal foot


Packaging:  
 16 pcs. per ctn.  
 1.92 sqs. per ctn. (17.8 m<sup>2</sup>)  
 Ship. wt: 109.2 lb (49.53 kg)



Sandstone  
 Canyon Clay  
 Pebble  
 Sage  
 Wicker

**PRODUCT CODE & DESCRIPTION**

**16312  
10" D-5  
Solid Soffit/  
Vertical Siding**




10" Exposure per Panel (254)  
10' Lengths (3048)  
.042" Nominal Thickness  
Light Roughsawn Texture

Packaging:  
24 pcs. per ctn.  
2 sqs. per ctn. (18.6 m<sup>2</sup>)  
Ship. wt: 83 lb (38 kg)

**COLORS**

Snow White  
Almond  
Antique Ivory  
Dover Gray  
Linen  
Maize  
Mist Blue  
Pearl  
Sandalwood

**16321  
10" D-5  
Solid Soffit/  
Vertical Siding**




10" Exposure per Panel (254)  
12' Lengths (3658)  
.042" Nominal Thickness  
Light Roughsawn Texture

Packaging:  
20 pcs. per ctn.  
2 sqs. per ctn. (18.6 m<sup>2</sup>)  
Ship. wt: 83 lb (38 kg)

Sandstone  
Canyon Clay  
Pebble  
Sage  
Wicker

**16320  
10" D-5  
Fully Vented Soffit**




10" Exposure per Panel (254)  
12' Lengths (3658)  
.042" Nominal Thickness  
Light Roughsawn Texture  
5.3 sq. inches ventilation  
per lineal foot

Packaging:  
20 pcs. per ctn.  
2 sqs. per ctn. (18.6 m<sup>2</sup>)  
Ship. wt: 83 lb (38 kg)

**PRODUCT CODE & DESCRIPTION**

**16345  
8" Solid Soffit**



8" Exposure per Panel (203.2)  
12'6" Lengths (3810)  
.042" Nominal Thickness  
Matte Texture


Packaging:  
12 pcs. per ctn.  
1 sq. per ctn. (9.29 m<sup>2</sup>)  
Ship. wt: 59 lb (27 kg)

\*Soffit use only.

**COLORS**

Snow White  
Linen  
Sandalwood  
Canyon Clay  
Pebble  
Wicker

**16346  
8" Vented Soffit**




8" Exposure per Panel (203.2)  
12'6" Lengths (3810)  
.042" Nominal Thickness  
Matte Texture  
2.4 sq. inches ventilation  
per lineal foot

Packaging:  
12 pcs. per ctn.  
1 sq. per ctn. (9.29 m<sup>2</sup>)  
Ship. wt: 59 lb (27 kg)

**PRODUCT CODE & DESCRIPTION**

**16550**  
**12" T-4**  
**Solid Soffit/  
 Vertical Siding**  
 12" Exposure per Panel (304.8)  
 12' Lengths (3658)  
 .040" Nominal Thickness  
 Brushed Texture




Packaging:  
 16 pcs. per ctn.  
 1.92 sqs. per ctn. (17.8 m<sup>2</sup>)  
 Ship. wt: 79 lb (36 kg)

**COLORS**


- Snow White
- Almond
- Antique Ivory
- Dover Gray
- Linen
- Maize
- Mist Blue
- Pearl
- Sandalwood
- Sandstone
- Canyon Clay
- Pebble
- Sage
- Wicker

**16570**  
**12" T-4**  
**Center Vented Soffit**  
 12" Exposure per Panel (304.8)  
 12' Lengths (3658)  
 .040" Nominal Thickness  
 Brushed Texture  
 2.3 sq. inches ventilation  
 per lineal foot



Packaging:  
 16 pcs. per ctn.  
 1.92 sqs. per ctn. (17.8 m<sup>2</sup>)  
 Ship. wt: 79 lb (36 kg)

**16590**  
**12" T-4**  
**Fully Vented Soffit**  
 12" Exposure per Panel (304.8)  
 12' Lengths (3658)  
 .040" Nominal Thickness  
 Brushed Texture  
 7.1 sq. inches ventilation  
 per lineal foot




Packaging:  
 16 pcs. per ctn.  
 1.92 sqs. per ctn. (17.8 m<sup>2</sup>)  
 Ship. wt: 79 lb (36 kg)

(For EnFusion Siding)

**PRODUCT CODE & DESCRIPTION**


**15522**  
**Inside Corner Post**  
 10' Lengths (3048)  
 Brushed Texture



Packaging:  
 10 pcs. per ctn.  
 100 lineal ft. per ctn. (30.5 m)  
 Ship. wt: 33.6 lb (15.3 kg)


See Matrix On  
 Pages 62-63.

**14518**  
**4" Outside Corner Post with Foam**  
 4" Face (101.6)  
 10' Lengths (3048)  
 Brushed Texture



Packaging:  
 10 pcs. per ctn.  
 100 lineal ft. per ctn. (30.5 m)  
 Ship. wt: 48.5 lb (22 kg)


**15003**  
**3-1/2" Window/Door Surround\* with Foam**  
 3-1/2" Face (88.9)  
 20' Lengths (6096)  
 Brushed Texture



Packaging:  
 10 pcs. per ctn.  
 200 lineal ft. per ctn. (61 m)  
 Ship. wt: 34.4 lb (15.6 kg)

\*Use understill trim (14078) as starter.

**K661945**  
**Easy Start Starter Strip**  
 12'6" Lengths (3810)



Packaging:  
 24 pcs. per ctn.  
 300 lineal ft. per ctn. (91.5 m)  
 Ship. wt: 32 lb (14.5 kg)


**PRODUCT CODE & DESCRIPTION**

**COLORS**

**14515**  
**3-1/2"**  
**Outside Corner Post**

3-1/2" Face (88.9)  
10' Lengths (3048)  
Brushed Texture


See Matrix On  
Pages 64-65.



Packaging:  
10 pcs. per ctn.  
100 lineal ft. per ctn. (30.5 m)  
Ship. wt: 41 lb (19 kg)

**14525**  
**3"**  
**Outside Corner Post**


3" Face (76.2)  
10' Lengths (3048)  
Brushed Texture



Packaging:  
10 pcs. per ctn.  
100 lineal ft. per ctn. (30.5 m)  
Ship. wt: 38 lb (17 kg)

**15030**  
**Bay & Bow**  
**Outside Corner Post**


2" Face (50.8)  
12'6" Lengths (3810)  
Matte Texture



Packaging:  
10 pcs. per ctn.  
125 lineal ft. per ctn. (38 m)  
Ship. wt: 23 lb (10.5 kg)

**14981**  
**6" Designer**  
**Outside Corner Post**

6" Face (152.4)  
20' Lengths (6096)  
Brushed Texture



Packaging:  
5 pcs. per ctn.  
100 lineal ft. per ctn. (30.5 m)  
Ship. wt: 56 lb (25 kg)


**PRODUCT CODE & DESCRIPTION**

**COLORS**

**15026**  
**7"**  
**Fluted Corner Post**  
**with Foam Insert**

20' Lengths (6096)  
Matte Texture


See Matrix On  
Pages 64-65.



Packaging:  
5 pcs. per ctn.  
100 lineal ft. per ctn. (30.5 m)  
Ship. wt: 87 lb (39.5 kg)

**15020**  
**Beaded Corner Post**  
**with Foam Insert**


20' Lengths (6096)  
Matte Texture



Packaging:  
5 pcs. per ctn.  
100 lineal ft. per ctn. (30.5 m)  
Ship. wt: 84 lb (38 kg)

**14992**  
**Beaded Corner Starter\***

20' Lengths (6096)  
Matte Texture




Packaging:  
10 pcs. per ctn.  
200 lineal ft. per ctn. (61 m)  
Ship. wt: 47.5 lb (21.5 kg)

\*Use with 3-1/2" window/door surround (14587) to create 3-piece corner.

**14110**  
**3/4" Inside Corner Post**

10' Lengths (3048)  
Brushed Texture



Packaging:  
10 pcs. per ctn.  
100 lineal ft. per ctn. (30.5 m)  
Ship. wt: 27.4 lb (12.4 kg)

**PRODUCT CODE & DESCRIPTION**


**COLORS**

**14098**  
**1/2" J-Channel**

12' Lengths (3658)  
Brushed Texture

See Matrix On  
Pages 64-65.


Packaging:  
40 pcs. per ctn.  
480 lineal ft. per ctn. (146.3 m)  
Ship. wt: 44 lb (20 kg)



**14057**  
**5/8" Premium J-Channel**

12' Lengths (3658)  
Brushed Texture


Packaging:  
40 pcs. per ctn.  
480 lineal ft. per ctn. (146.3 m)  
Ship. wt: 46 lb (21 kg)



**14095**  
**3/4" Premium J-Channel**

12' Lengths (3658)  
Brushed Texture


Packaging:  
40 pcs. per ctn.  
480 lineal ft. per ctn. (146.3 m)  
Ship. wt: 49 lb (22 kg)



**14092**  
**1-1/8" J-Channel**

12' Lengths (3658)  
Brushed Texture

Packaging:  
40 pcs. per ctn.  
480 lineal ft. per ctn. (146.3 m)  
Ship. wt: 50 lb (22.6 kg)



**PRODUCT CODE & DESCRIPTION**


**COLORS**

**14061** (Special Order)  
**1-1/4" J-Channel**

12' Lengths (3658)  
Brushed Texture

See Matrix On  
Pages 64-65.


Packaging:  
36 pcs. per ctn.  
432 lineal ft. per ctn. (131.7 m)  
Ship. wt: 54 lb (24.4 kg)



**14072** (Special Order)  
**1-1/2" J-Channel**

12' Lengths (3658)  
Brushed Texture


Packaging:  
30 pcs. per ctn.  
360 lineal ft. per ctn. (109.8 m)  
Ship. wt: 56.4 lb (25.6 kg)



**14093**  
**2-1/2" Wide Face J-Channel**

12' Lengths (3658)  
Brushed Texture


Packaging:  
18 pcs. per ctn.  
216 lineal ft. per ctn. (65.8 m)  
Ship. wt: 47 lb (21 kg)



**14078**  
**Undersill Trim\***

12' Lengths (3658)  
Brushed Texture

Packaging:  
40 pcs. per ctn.  
480 lineal ft. per ctn. (146.3 m)  
Ship. wt: 37 lb (16.8 kg)




\*Also used as a starter strip for 5" lineal.

**PRODUCT CODE & DESCRIPTION**

**14990**  
**Double Undersill Trim**

12' Lengths (3658)  
Smooth Texture

Packaging:  
25 pcs. per ctn.  
300 lineal ft. per ctn. (91.5 m)  
Ship. wt: 35 lb (16 kg)




**COLORS**

See Matrix On  
Pages 64-65.

**14983**  
**Drip Cap**

12' Lengths (3658)  
Brushed Texture


Packaging:  
45 pcs. per ctn.  
540 lineal ft. per ctn. (164.6 m)  
Ship. wt: 71 lb (32.2 kg)



**14142**  
**Beltline Trim**

12' Lengths (3658)  
Brushed Texture


Packaging:  
30 pcs. per ctn.  
360 lineal ft. per ctn. (109.7 m)  
Ship. wt: 39 lb (18 kg)



**14587**  
**3-1/2" Window/Door Surround\***

3-1/2" Face (88.9)  
20' Lengths (6096)  
Matte Texture

Packaging:  
5 pcs. per ctn.  
100 lineal ft. per ctn. (30.5 m)  
Ship. wt: 30 lb (13.5 kg)




\*Use with surround starter (14989).

**PRODUCT CODE & DESCRIPTION**

**15005**  
**5" Window/Door Lineal\***

5" Face (127)  
20' Lengths (6096)  
Matte Texture

Packaging:  
10 pcs. per ctn.  
200 lineal ft. per ctn. (61 m)  
Ship. wt: 65 lb (29.5 kg)




\*Use undersill trim (14078) as starter.

**14989**  
**Surround Starter**

12' Lengths (3658)


Packaging:  
25 pcs. per ctn.  
300 lineal ft. per ctn. (91.4 m)  
Ship. wt: 33 lb (15 kg)



**15010**  
**5" Fluted Lineal**

20' Lengths (6096)  
Matte Texture


Packaging:  
10 pcs. per ctn.  
200 lineal ft. per ctn. (61 m)  
Ship. wt: 70 lb (32 kg)



**14980**  
**Starter Strip\***

12' Lengths (3658)

Packaging:  
40 pcs. per ctn.  
480 lineal ft. per ctn. (146.3 m)  
Ship. wt: 58 lb (26 kg)



\*For Sequoia Select vinyl siding, use aluminum starter strip (0109025) located on page 41.

**PRODUCT CODE & DESCRIPTION**


**COLORS**

**14094**  
**F-Channel**

12' Lengths (3658)  
Brushed Texture

See Matrix On  
Pages 64-65.


Packaging:  
24 pcs. per ctn.  
288 lineal ft. per ctn. (87.8 m)  
Ship. wt: 43 lb (19.6 kg)



**14086**  
**3/4" F-Channel**

12'6" Lengths (3810)  
Brushed Texture


Packaging:  
32 pcs. per ctn.  
400 lineal ft. per ctn. (122 m)  
Ship. wt: 55 lb (25 kg)



**14986**  
**3/8" Soffit Cove**  
**J-Channel**

12'6" Lengths (3810)  
Matte Texture


Packaging:  
24 pcs. per ctn.  
300 lineal ft. per ctn. (91.5 m)  
Ship. wt: 39.7 lb (18 kg)



**14099**  
**Soffit Double Channel**

12' Lengths (3658)  
Brushed Texture

Packaging:  
20 pcs. per ctn.  
240 lineal ft. per ctn. (73.2 m)  
Ship. wt: 48 lb (22 kg)



**PRODUCT CODE & DESCRIPTION**


**COLORS**

**15035**  
**3-1/2" H-Trim**

20' Lengths (6096)  
Matte Texture

See Matrix On  
Pages 64-65.


Packaging:  
10 pcs. per ctn.  
200 lineal ft. per ctn. (61 m)  
Ship. wt: 64 lb (29 kg)



**14131**  
**Soffit Cove Moulding**

12' Lengths (3658)  
Brushed Texture


Packaging:  
16 pcs. per ctn.  
192 lineal ft. per ctn. (15.52 m)  
Ship. wt: 30.4 lb (14 kg)



**14982**  
**Soffit Crown Moulding**

12' Lengths (3658)  
Brushed Texture

Packaging:  
18 pcs. per ctn.  
216 lineal ft. per ctn. (65.9 m)  
Ship. wt: 48 lb (18.2 kg)




**PRODUCT CODE & DESCRIPTION**

**COLORS**

**14516**  
**Variegated**  
**3-1/2" Outside**  
**Corner Post**

3-1/2" Face (88.9)  
 10' Lengths (3048)  
 Brushed Texture  
 See Matrix On  
 Pages 64-65.


Packaging:  
 10 pcs. per ctn.  
 100 lineal ft. per ctn. (30.5 m)  
 Ship. wt: 44 lb (20 kg)



**14521**  
**Variegated**  
**1/2" J-Channel**

12' Lengths (3658)  
 Brushed Texture


Packaging:  
 40 pcs. per ctn.  
 480 lineal ft. per ctn. (146.3 m)  
 Ship. wt: 45 lb (20.4 kg)



**14519**  
**Variegated**  
**3/4" J-Channel**

12' Lengths (3658)  
 Brushed Texture


Packaging:  
 40 pcs. per ctn.  
 480 lineal ft. per ctn. (146.3 m)  
 Ship. wt: 49 lb (22 kg)



**14522**  
**Variegated**  
**Undersill Trim**

12' Lengths (3658)  
 Brushed Texture

Packaging:  
 40 pcs. per ctn.  
 480 lineal ft. per ctn. (146.3 m)  
 Ship. wt: 37 lb (16.8 kg)




**PRODUCT CODE & DESCRIPTION**

**COLORS**

**14520**  
**Variegated Drip Cap**

12' Lengths (3658)  
 Brushed Texture  
 See Matrix On  
 Pages 64-65.

Packaging:  
 45 pcs. per ctn.  
 540 lineal ft. per ctn. (164.6 m)  
 Ship. wt: 55 lb (25 kg)






CEDARWOOD®

ALUMINUM SIDING

ALUMINUM SIDING

**PRODUCT CODE & DESCRIPTION**

**0010008**  
**Double 5"**  
1/2" Butt (12.7)  
2-5" Exposure per Panel (127/254)  
12' Lengths (3658)  
PVDF Finish  
Woodgrain Texture



Packaging:  
20 pcs. per ctn.  
2 sqs. per ctn. (18.58 m<sup>2</sup>)  
Ship. wt: 89 lb (40.5 kg)

**COLORS**

Aspen Gray  
Chestnut Brown  
Maple Tan  
Tawny Oak




DELUXE™

ALUMINUM SIDING

ALUMINUM SIDING

**PRODUCT CODE & DESCRIPTION**

**0001012**  
**Double 4"**  
1/2" Butt (12.7)  
2-4" Exposure per Panel (101.6/203.2)  
12'6" Lengths (3810)  
Poly Finish  
Smooth Texture



Packaging:  
24 pcs. per ctn.  
2 sqs. per ctn. (18.58 m<sup>2</sup>)  
Ship. wt: 73 lb (33.3 kg)

**COLORS**

Bright White



WOODGRAIN™ SERIES 2000

ALUMINUM SIDING

ALUMINUM SIDING

**PRODUCT CODE & DESCRIPTION**

**0008201**  
**Double 4"**  
1/2" Butt (12.7)  
2-4" Exposure per Panel (101.6/203.2)  
12'6" Lengths (3810)  
Poly Finish  
Woodgrain Texture




Packaging:  
24 pcs. per ctn.  
2 sqs. per ctn. (18.58 m<sup>2</sup>)  
Ship. wt: 70 lb (31.8 kg)

**COLORS**

Bright White  
Almond  
Antique Ivory  
Canyon Clay  
Dover Gray  
Sandstone  
Wicker

**0001011**  
**8"**

1/2" Butt (12.7)  
8" Exposure per Panel (203.2)  
12'6" Lengths (3810)  
Poly Finish  
Smooth Texture




Packaging:  
24 pcs. per ctn.  
2 sqs. per ctn. (18.58 m<sup>2</sup>)  
Ship. wt: 84 lb (38.4 kg)

**PRODUCT CODE & DESCRIPTION**

**0520036**  
**12" T-4**  
**Solid**

12" Exposure per Panel (304.8)  
 12' Lengths (3658)  
 Poly Finish  
 Smooth Texture


Packaging:  
 16 pcs. per ctn.  
 1.92 sqs. per ctn. (17.8 m<sup>2</sup>)  
 Ship. wt: 56 lb (25.5 kg)



**0516036**  
**12" T-4**  
**Center Vented**

12" Exposure per Panel (304.8)  
 12' Lengths (3658)  
 Poly Finish  
 Smooth Texture  
 3.9 sq. inches ventilation  
 per lineal foot


Packaging:  
 16 pcs. per ctn.  
 1.92 sqs. per ctn. (17.8 m<sup>2</sup>)  
 Ship. wt: 56 lb (25.5 kg)



**0515036**  
**12" T-4**  
**Fully Vented**

12" Exposure per Panel (304.8)  
 12' Lengths (3658)  
 Poly Finish  
 Smooth Texture  
 11.6 sq. inches ventilation  
 per lineal foot

Packaging:  
 16 pcs. per ctn.  
 1.92 sqs. per ctn. (17.8 m<sup>2</sup>)  
 Ship. wt: 56 lb (25.5 kg)



**COLORS**


- Bright White
- Almond
- Antique Ivory
- Black
- Bronze
- Brownstone
- Canyon Clay
- Classic Brown
- Dover Gray
- Grecian Green
- Linen
- London Brown
- Musket Brown
- Norwood
- Pebble
- Royal Brown
- Sage
- Sandstone
- Terratone
- Thistle
- Venetian Red
- White
- Wicker

**PRODUCT CODE & DESCRIPTION**

**0540663**  
**16" Quad-4**  
**Solid**

16" Exposure per Panel (406.4)  
 12' Lengths (3658)  
 Poly Finish  
 Smooth Texture


Packaging:  
 12 pcs. per ctn.  
 1.92 sqs. per ctn. (17.8 m<sup>2</sup>)  
 Ship. wt: 54 lb (24.5 kg)



**0540661**  
**16" Quad-4**  
**Center Vented**

16" Exposure per Panel (406.4)  
 12' Lengths (3658)  
 Poly Finish  
 Smooth Texture  
 7.8 sq. inches ventilation  
 per lineal foot


Packaging:  
 12 pcs. per ctn.  
 1.92 sqs. per ctn. (17.8 m<sup>2</sup>)  
 Ship. wt: 54 lb (24.5 kg)



**0540665**  
**16" Quad-4**  
**Fully Vented**

16" Exposure per Panel (406.4)  
 12' Lengths (3658)  
 Poly Finish  
 Smooth Texture  
 15.5 sq. inches ventilation  
 per lineal foot

Packaging:  
 12 pcs. per ctn.  
 1.92 sqs. per ctn. (17.8 m<sup>2</sup>)  
 Ship. wt: 54 lb (24.5 kg)



**COLORS**

- Bright White
- Almond
- Antique Ivory
- Brownstone
- Canyon Clay
- Charcoal
- Classic Brown
- Dover Gray
- Grecian Green
- Linen
- London Brown
- Musket Brown
- Norwood
- Pebble
- Royal Brown
- Sage
- Sandstone
- Terratone
- Thistle
- Venetian Red
- White
- Wicker


**PRODUCT CODE & DESCRIPTION**

**COLORS**

**0522015**  
**16" Quad-4**  
**Solid**  
 16" Exposure per Panel (406.4)  
 12' Lengths (3658)  
 PVC Finish  
 Striated Texture

Bright White


Packaging:  
 12 pcs. per ctn.  
 1.92 sqs. per ctn. (17.8 m<sup>2</sup>)  
 Ship. wt: 59 lb (26 kg)



**0517015**  
**16" Quad-4**  
**Center Vented**

16" Exposure per Panel (406.4)  
 12' Lengths (3658)  
 PVC Finish  
 Striated Texture  
 7.8 sq. inches ventilation  
 per lineal foot


Packaging:  
 12 pcs. per ctn.  
 1.92 sqs. per ctn. (17.8 m<sup>2</sup>)  
 Ship. wt: 59 lbs (26 kg)



**0518015**  
**16" Quad-4**  
**Fully Vented**

16" Exposure per Panel (406.4)  
 12' Lengths (3658)  
 PVC Finish  
 Striated Texture  
 15.5 sq. inches ventilation  
 per lineal foot

Packaging:  
 12 pcs. per ctn.  
 1.92 sqs. per ctn. (17.8 m<sup>2</sup>)  
 Ship. wt: 59 lb (26 kg)




**PRODUCT CODE & DESCRIPTION**

**COLORS**

**0520130**  
**12" T-4**  
**Solid**  
 12" Exposure per Panel (304.8)  
 12' Lengths (3658)  
 Poly Finish  
 Smooth Texture

Bright White


Packaging:  
 16 pcs. per ctn.  
 1.92 sqs. per ctn. (17.8 m<sup>2</sup>)  
 Ship. wt: 44 lb (20 kg)



**0516130**  
**12" T-4**  
**Center Vented**

12" Exposure per Panel (304.8)  
 12' Lengths (3658)  
 Poly Finish  
 Smooth Texture  
 3.9 sq. inches ventilation  
 per lineal foot

Packaging:  
 16 pcs. per ctn.  
 1.92 sqs. per ctn. (17.8 m<sup>2</sup>)  
 Ship. wt: 44 lb (20 kg)




## DELUXE™ ALUMINUM FASCIA

### PRODUCT CODE & DESCRIPTION

**0525006**  
**6" Fascia**

12'6" Lengths (3810)  
Poly Finish  
Smooth Texture


Packaging:  
24 pcs. per ctn.  
300 lineal ft. per ctn. (91.5 m)  
Ship. wt: 64 lb (29.1 kg)



**0525008**  
**8" Fascia**

12'6" Lengths (3810)  
Poly Finish  
Smooth Texture

Packaging:  
24 pcs. per ctn.  
300 lineal ft. per ctn. (91.5 m)  
Ship. wt: 80 lb (36.4 kg)



### COLORS

Bright White

---

Almond  
Antique Ivory  
Black  
Bronze  
Brownstone  
Canyon Clay  
Charcoal  
Classic Brown  
Dover Gray  
Grecian Green  
Linen  
London Brown  
Musket Brown  
Norwood  
Pebble  
Royal Brown  
Sage  
Sandstone  
Terratone  
Thistle  
Venetian Red  
White  
Wicker


## VALUGARD™ ALUMINUM FASCIA

### PRODUCT CODE & DESCRIPTION

**0525016**  
**6" Fascia**

12'6" Lengths (3810)  
Poly Finish  
Smooth Texture

Packaging:  
24 pcs. per ctn.  
300 lineal ft. per ctn. (91.5 m)  
Ship. wt: 48 lb (21.8 kg)



### COLORS


Bright White

**PRODUCT CODE & DESCRIPTION**

**0103501**  
**Deluxe™**  
**Outside Corner Post**

2-1/2" Face (63.5)  
 10' Lengths (3048)  
 Poly Finish  
 Smooth Texture


Packaging:  
 10 pcs. per ctn.  
 100 lineal ft. per ctn. (30.5 m)  
 Ship. wt: 35 lb (15.9 kg)



**0103508**  
**Woodgrain™**  
**Outside Corner Post**

2-1/2" Face (63.5)  
 10' Lengths (3048)  
 Poly Finish  
 Woodgrain Texture


Packaging:  
 10 pcs. per ctn.  
 100 lineal ft. per ctn. (30.5 m)  
 Ship. wt: 35 lb (15.9 kg)



**0104209**  
**3/4" J-Channel**

12' Lengths (3658)  
 Poly Finish  
 Smooth Texture


Packaging:  
 40 pcs. per ctn.  
 480 lineal ft. per ctn. (146.3 m)  
 Ship. wt: 29 lb (13 kg)



**0108609**  
**Snap-Lock**  
**Finish Trim**

12' Lengths (3658)  
 Poly Finish  
 Smooth Texture

Packaging:  
 40 pcs. per ctn.  
 480 lineal ft. per ctn. (146.3 m)  
 Ship. wt: 25 lb (11.4 kg)



**COLORS**

See Matrix On  
 Pages 69-69.


**PRODUCT CODE & DESCRIPTION**

**0109025**  
**2-1/2" Starter Strip**

10' Lengths (3048)

See Matrix On  
 Pages 68-69.


Packaging:  
 50 pcs. per ctn.  
 500 lineal ft. per ctn. (152.4 m)  
 Ship. wt: 50 lb (22.7 kg)



**0103510**  
**Cedarwood®**  
**Outside Corner Post**

2-1/2" Face (63.5)  
 10' Lengths (3048)  
 PVDF Finish  
 Woodgrain Texture


Packaging:  
 10 pcs. per ctn.  
 100 lineal ft. per ctn. (30.5 m)  
 Ship. wt: 35 lb (15.9 kg)



**0104219**  
**Cedarwood®**  
**3/4" J-Channel**

12' Lengths (3658)  
 PVDF Finish  
 Smooth Texture


Packaging:  
 40 pcs. per ctn.  
 480 lineal ft. per ctn. (146.3 m)  
 Ship. wt: 29 lb (13.2 kg)



**0108619**  
**Cedarwood®**  
**Snap-Lock Finish Trim**

12' Lengths (3658)  
 PVDF Finish  
 Smooth Texture

Packaging:  
 40 pcs. per ctn.  
 480 lineal ft. per ctn. (146.3 m)  
 Ship. wt: 25 lb (11.4 kg)




**PRODUCT CODE & DESCRIPTION**

**0199033**  
**Cedarwood®**  
**Touch-Up Paint**

Packaging:  
 6 pcs. per ctn.  
 Ship. wt: 1 lb (0.5 kg)

**COLORS**


See Matrix On  
 Pages 68-69.



**0530001**  
**Cedarwood®**  
**Cove Moulding**

12'6" Lengths (3810)  
 Poly Finish  
 Smooth Texture


Packaging:  
 24 pcs. per ctn.  
 300 lineal ft. per ctn. (91.5 m)  
 Ship. wt: 35 lb (16 kg)



**0530002**  
**Reverse Frieze**  
**Moulding**

12'6" Lengths (3810)  
 Poly Finish  
 Smooth Texture


Packaging:  
 24 pcs. per ctn.  
 300 lineal ft. per ctn. (91.5 m)  
 Ship. wt: 39.5 lb (18 kg)



**0531002**  
**Reverse Frieze**  
**Moulding**

12'6" Lengths (3810)  
 PVC Finish  
 Striated Texture

Packaging:  
 24 pcs. per ctn.  
 300 lineal ft. per ctn. (91.5 m)  
 Ship. wt: 41.5 lb (18.8 kg)




**PRODUCT CODE & DESCRIPTION**

**0530008**  
**1/2" Soffit J-Channel**

12'6" Lengths (3810)  
 Poly Finish  
 Smooth Texture

See Matrix On  
 Pages 68-69.


Packaging:  
 40 pcs. per ctn.  
 500 lineal ft. per ctn. (152.4 m)  
 Ship. wt: 34.6 lb (16 kg)



**0531008**  
**1/2" Soffit J-Channel**

12'6" Lengths (3810)  
 PVC Finish  
 Striated Texture


Packaging:  
 40 pcs. per ctn.  
 500 lineal ft. per ctn. (152.4 m)  
 Ship. wt: 37 lb (16.8 kg)



**0530015**  
**Drip Edge Style D**


10' Lengths (3048)  
 Poly Finish  
 Smooth Texture

Packaging:  
 25 pcs. per ctn.  
 250 lineal ft. per ctn. (76.2 m)  
 Ship. wt: 29.2 lb (13 kg)



**PRODUCT CODE & DESCRIPTION**

**1726102**  
**Double 4"**  
1/2" Butt (12.7)  
2-4" Exposure per Panel  
(101.6/203.2)  
12'6" Lengths (3810)  
PVC Finish  
Woodgrain Texture




Packaging:  
12 pcs. per ctn.  
1 sq. per ctn. (9.29 m<sup>2</sup>)  
Ship. wt: 95 lb (43 kg)

**COLORS**

Bright White  
Almond  
Antique Ivory  
Brownstone  
Canyon Clay  
Classic Brown  
Dover Gray  
Norwood  
Sage

**1726101**  
**8"**  
1/2" Butt (12.7)  
8" Exposure per Panel (203.2)  
12'6" Lengths (3810)  
PVC Finish  
Woodgrain Texture




Packaging:  
12 pcs. per ctn.  
1 sq. per ctn. (9.29 m<sup>2</sup>)  
Ship. wt: 91 lb (41 kg)

Thistle  
Venetian Red  
Wicker

**PRODUCT CODE & DESCRIPTION**


**1751104**  
**Double 5"**  
1/2" Butt (12.7)  
2-5" Exposure per Panel (127/254)  
12' Lengths (3658)  
PVC Finish  
Woodgrain Texture



Packaging:  
10 pcs. per ctn.  
1 sq. per ctn. (9.29 m<sup>2</sup>)  
Ship. wt: 91 lb (41 kg)

Bright White  
Almond  
Antique Ivory  
Brownstone  
Canyon Clay  
Classic Brown  
Dover Gray  
Norwood  
Sage

**1751101**  
**8"**  
1/2" Butt (12.7)  
8" Exposure per Panel (203.2)  
12'6" Lengths (3810)  
PVC Finish  
Woodgrain Texture




Packaging:  
12 pcs. per ctn.  
1 sq. per ctn. (9.29 m<sup>2</sup>)  
Ship. wt: 91 lb (41 kg)

Thistle  
Venetian Red  
Wicker

**PRODUCT CODE & DESCRIPTION**

**1757104**  
**Double 5"**  
1/2" Butt (12.7)  
2-5" Exposure per Panel (127/254)  
12' Lengths (3658)  
PVC Fusion Finish  
Woodgrain Texture




Packaging:  
10 pcs. per ctn.  
1 sq. per ctn. (9.29 m<sup>2</sup>)  
Ship. wt: 95 lb (43 kg)

**COLORS**

Poplar  
Southern Pecan  
Sycamore  
Winter Oak

**PRODUCT CODE & DESCRIPTION**

**1719010**  
**Universal™**  
**Double 5"**  
**Dutch Lap**  
1/2" Butt (12.7)  
2-5" Exposure per Panel (127/254)  
12' Lengths (3658)  
PVC Finish  
Woodgrain Texture




Packaging:  
10 pcs. per ctn.  
1 sq. per ctn. (9.29 m<sup>2</sup>)  
Ship. wt: 91 lb (41 kg)

**COLORS**

Bright White  
Almond  
Antique Ivory  
Brownstone  
Canyon Clay  
Classic Brown  
Dover Gray  
Norwood  
Sage  
Thistle  
Venetian Red  
Wicker

**1719006**  
**Universal™**  
**12" Vertical**  
**Board & Batten**



5/8" Batten Height (15.9)  
2" Batten Width (50.8)  
12" Exposure per Panel (304.8)  
10' Lengths (3048)  
PVC Finish  
Medium Woodgrain Texture

Packaging:  
10 pcs. per ctn.  
1 sq. per ctn. (9.29 m<sup>2</sup>)  
Ship. wt: 85 lb (39 kg)

**PRODUCT CODE & DESCRIPTION**


**COLORS**

**1855104**  
**4" Steel Fascia**

10' Lengths (3048)  
PVC Finish  
Woodgrain Texture

See Matrix On  
Pages 70-71.


Packaging:  
12 pcs. per ctn.  
120 lineal ft. per ctn. (36.6 m)  
Ship. wt: 39 lb (18 kg)



**1855106**  
**6" Steel Fascia**

10' Lengths (3048)  
PVC Finish  
Woodgrain Texture


Packaging:  
12 pcs. per ctn.  
120 lineal ft. per ctn. (36.6 m)  
Ship. wt: 51 lb (23 kg)



**1855108**  
**8" Steel Fascia**

10' Lengths (3048)  
PVC Finish  
Woodgrain Texture


Packaging:  
12 pcs. per ctn.  
120 lineal ft. per ctn. (36.6 m)  
Ship. wt: 64 lb (29 kg)



**1855110**  
**10" Steel Fascia**

10' Lengths (3048)  
PVC Finish  
Woodgrain Texture

Packaging:  
12 pcs. per ctn.  
120 lineal ft. per ctn. (36.6 m)  
Ship. wt: 77 lb (35 kg)



**PRODUCT CODE & DESCRIPTION**


**COLORS**

**1813526**  
**3/4" Outside  
Corner Post**

2-1/2" Face (63.5)  
10' Lengths (3048)  
PVC Finish  
Woodgrain Texture

See Matrix On  
Pages 72-73.


Packaging:  
10 pcs. per ctn.  
100 lineal ft. per ctn. (30.5 m)  
Ship. wt: 62 lb (28 kg)



**1813026**  
**1-1/8" Outside  
Corner Post**

2-1/2" Face (63.5)  
10' Lengths (3048)  
PVC Finish  
Woodgrain Texture


Packaging:  
10 pcs. per ctn.  
100 lineal ft. per ctn. (30.5 m)  
Ship. wt: 64 lb (29 kg)



**1814206**  
**3/4" J-Channel**

12'6" Lengths (3810)  
PVC Finish  
Striated Texture


Packaging:  
24 pcs. per ctn.  
300 lineal ft. per ctn. (91.5 m)  
Ship. wt: 48 lb (22 kg)



**1814106**  
**1-1/8" J-Channel**

12'6" Lengths (3810)  
PVC Finish  
Striated Texture

Packaging:  
24 pcs. per ctn.  
300 lineal ft. per ctn. (91.5 m)  
Ship. wt: 54 lb (25 kg)



**PRODUCT CODE & DESCRIPTION**


**COLORS**

**1815011  
Snap-Lock Finish Trim**

12'6" Lengths (3810)  
PVC Finish  
Striated Texture

See Matrix On  
Pages 72-73.


Packaging:  
24 pcs. per ctn.  
300 lineal ft. per ctn. (91.5 m)  
Ship. wt: 35 lb (16 kg)



**1829020  
2-1/2" Starter Strip**

10' Lengths (3048)


Packaging:  
26 pcs. per ctn.  
260 lineal ft. per ctn. (79.3 m)  
Ship. wt: 48 lb (22 kg)



**1829025  
3-1/2" Starter Strip**

10' Lengths (3048)


Packaging:  
26 pcs. per ctn.  
260 lineal ft. per ctn. (79.3 m)  
Ship. wt: 61 lb (28 kg)



**1815015  
Driftwood® Snap-Lock  
Finish Trim**

12'6" Lengths (3810)  
PVC Fusion Finish  
Smooth Texture

Packaging:  
24 pcs. per ctn.  
300 lineal ft. per ctn. (91.5 m)  
Ship. wt: 35 lb (16 kg)



**PRODUCT CODE & DESCRIPTION**


**COLORS**

**1823650  
Driftwood®  
3/4" Outside  
Corner Post**

2-1/2" Face (63.5)  
10' Lengths (3048)  
PVC Fusion Finish  
Woodgrain Texture

See Matrix On  
Pages 72-73.


Packaging:  
10 pcs. per ctn.  
100 lineal ft. per ctn. (30.5 m)  
Ship. wt: 62 lb (28 kg)



**1823150  
Driftwood®  
1-1/8" Outside  
Corner Post**

2-1/2" Face (63.5)  
10' Lengths (3048)  
PVC Fusion Finish  
Woodgrain Texture


Packaging:  
10 pcs. per ctn.  
100 lineal ft. per ctn. (30.5 m)  
Ship. wt: 64 lb (29 kg)



**1824320  
Driftwood®  
3/4" J-Channel**

12'6" Lengths (3810)  
PVC Fusion Finish  
Smooth Texture


Packaging:  
24 pcs. per ctn.  
300 lineal ft. per ctn. (91.5 m)  
Ship. wt: 48 lb (22 kg)



**1824220  
Driftwood®  
1-1/8" J-Channel**

12'6" Lengths (3810)  
PVC Fusion Finish  
Smooth Texture

Packaging:  
24 pcs. per ctn.  
300 lineal ft. per ctn. (91.5 m)  
Ship. wt: 54 lb (25 kg)



**PRODUCT CODE & DESCRIPTION****COLORS**

0710117  
**24" MarrFree™**

50' Lengths (15.24 m)  
MarrFree Finish

See Matrix On  
Pages 74-75.

Packaging:  
1 pc. per ctn.  
Ship. wt: 28.1 lb (13 kg)



0737407  
**24" LoMar Heavy-Duty  
Bright White Over  
Bright White**

50' Lengths (15.24 m)  
LoMar Finish

Packaging:  
1 pc. per ctn.  
Ship. wt: 33.8 lb (15 kg)



0737107  
**24" LoMar  
Color Over Bright White**

50' Lengths (15.24 m)  
LoMar Finish

Packaging:  
1 pc. per ctn.  
Ship. wt: 27.3 lb (12 kg)



0735007  
**24" LoMar  
White Over White**

50' Lengths (15.24 m)  
LoMar Finish

Packaging:  
1 pc. per ctn.  
Ship. wt: 27.3 lb (12 kg)

**PRODUCT CODE & DESCRIPTION****COLORS**

0736007  
**24" LoMar  
Polar White Over  
Polar White**

50' Lengths (15.24 m)  
LoMar Finish

See Matrix On  
Pages 74-75.

Packaging:  
1 pc. per ctn.  
Ship. wt: 27.3 lb (12 kg)



0714007  
**24" Cedarwood®  
Over Solid Color**

50' Lengths (15.24 m)  
PVDF Finish

Packaging:  
1 pc. per ctn.  
Ship. wt: 26 lb (12 kg)



0710007  
**24" PVC Coated Color,  
1 Side**

50' Lengths (15.24 m)  
PVC Finish

Packaging:  
1 pc. per ctn.  
Ship. wt: 27.7 lb (13 kg)



## TRIM COIL | ALUMINUM – VALUGARD

### PRODUCT CODE & DESCRIPTION

### COLORS

0739010  
**24" ValuGard™  
Bright White Over  
Bright White**

50' Lengths (15.24 m)  
Poly Finish

See Matrix On  
Pages 74-75.

Packaging:  
1 pc. per ctn.  
Ship. wt: 23 lb (10.4 kg)



0710010  
**24" ValuGard™  
Bright White, 1 Side**

50' Lengths (15.24 m)  
PVC Finish

Packaging:  
1 pc. per ctn.  
Ship. wt: 26 lb (11.8 kg)



## TRIM COIL | STEEL

### PRODUCT CODE & DESCRIPTION


### COLORS

1870007  
**22.3" PVC  
Color, 1 Side**

50' Lengths (15.24 m)  
PVC Finish

See Matrix On  
Pages 74-75.

Packaging:  
1 pc. per ctn.  
Ship. wt: 63 lb (28.6 kg)



1870010  
**22.3" Driftwood®  
Color, 1 Side**

50' Lengths (15.24 m)  
PVC Fusion Finish

Packaging:  
1 pc. per ctn.  
Ship. wt: 63 lb (28.6 kg)



## GUTTER COIL | ALUMINUM

### PRODUCT CODE & DESCRIPTION

### COLORS

0200015  
**Gutter Coil**  
.027" x 11.75"

Poly Finish

See Matrix On  
Pages 78-79.

Packaging:  
2 rolls per skid  
350/700 lb per skid  
Ship. wt: 700 lb (317.5 kg)



0200020  
**Gutter Coil**  
.027" x 11.875"

Poly Finish

Packaging:  
2 rolls per skid  
350/700 lb per skid  
Ship. wt: 700 lb (317.5 kg)



0220012  
**Gutter Coil**  
.027" x 11.875"

Poly Finish

Packaging:  
2 rolls per skid  
200/400 lb per skid  
Ship. wt: 400 lb (181.4 kg)



### PRODUCT CODE & DESCRIPTION

### COLORS

0200035  
**Gutter Coil**  
.032" x 11.75"

Poly Finish

See Matrix On  
Pages 78-79.

Packaging:  
2 rolls per skid  
350/700 lb per skid  
Ship. wt: 700 lb (317.5 kg)



0200040  
**Gutter Coil**  
.032" x 11.875"

Poly Finish

Packaging:  
2 rolls per skid  
350/700 lb per skid  
Ship. wt: 700 lb (317.5 kg)



0220022  
**Gutter Coil**  
.032" x 11.875"

Poly Finish

Packaging:  
2 rolls per skid  
200/400 lb per skid  
Ship. wt: 400 lb (181.4 kg)





## SHAKES & SCALLOPS VINYL SOFFIT

	751 Snow White	004 Almond	007 Antique Ivory	150 Dover Gray	449 Linen	479 Maize	505 Mist Blue	618 Pearl	725 Sandalwood	724 Sandstone	088 Canyon Clay	307 Pebble
<b>Fairhaven Sound Single Select*</b>												
Traditional Shake	●	●	●	●	●	●		●		●	●	●
Scallop	●	●	●	●	●	●		●		●	●	●
Cape Cod Shingle	●	●	●	●	●	●		●		●	●	●
Hand-Split Shake	●	●	●	●	●	●		●		●	●	●
Traditional Shake Corner Piece	●	●	●	●	●	●		●		●	●	●
Hand-Split Shake Corner Piece	●	●	●	●	●	●		●		●	●	●
Starter Strip												
AccuClip												

	751 Snow White	004 Almond	007 Antique Ivory	150 Dover Gray	449 Linen	479 Maize	505 Mist Blue	618 Pearl	725 Sandalwood	724 Sandstone	088 Canyon Clay	307 Pebble
<b>Soffit &amp; Vertical Siding</b>												
Sequoia Select Ultra-Premium 12"	●	●	●	●	●	●	●	●	●	●	●	●
Oxford Premium 10"	●	●	●	●	●	●	●	●	●	●	●	●
Beaded Premium 8"	●				●				●		●	●
Fairweather 12"	●	●	●	●	●	●	●	●	●	●	●	●

## COLOR MATRIX

	Darker Colors												
624 Sage	●	●	●	●	●	●	●	●	●	●	●	●	
840 Wicker	●	●	●	●	●	●	●	●	●	●	●	●	
665 Dark Drift	●	●	●	●	●	●	●	●	●	●	●	●	
660 Harvest Wheat	●	●	●	●	●	●	●	●	●	●	●	●	
652 Midnight Surf	●	●	●	●	●	●	●	●	●	●	●	●	
653 Moonlit Moss	●	●	●	●	●	●	●	●	●	●	●	●	
666 Saddle Brown	●	●	●	●	●	●	●	●	●	●	●	●	
120 Venetian Red	●	●	●	●	●	●	●	●	●	●	●	●	
651 Windswept Smoke	●	●	●	●	●	●	●	●	●	●	●	●	
No Color													●

624 Sage	●	●
840 Wicker	●	●

## DEEP-POCKET INSULATED VINYL ACCESSORIES

		751 Snow White	004 Almond	007 Antique Ivory	150 Dover Gray	088 Canyon Clay	307 Pebble	624 Sage	840 Wicker
Inside Corner Post	15522	●	●	●	●	●	●	●	●
4" Outside Corner Post w/ Foam	14518	●	●	●	●	●	●	●	●
3-1/2" Win/Door Surround* w/ Foam	15003	●	●		●		●		●
Easy Start Starter Strip	K661945								

## COLOR MATRIX

Designer Colors									
665 Dark Drift	660 Harvest Wheat	652 Midnight Surf	653 Moonlit Moss	666 Saddle Brown	120 Venetian Red	651 W. Smoke	No Color		
●	●	●	●	●	●	●			
●	●	●	●	●	●	●			
									●







# STEEL SIDING & FASCIA COLOR MATRIX

	004 Almond	007 Antique Ivory	068 Bright White	064 Bronze	418 Brownstone	088 Canyon Clay	121 Classic Brown	151 Dover Gray	258 Grecian Green	449 Linen	372 London Brown	R60 Norwood	307 Pebble
<b>SteelTek</b>													
Double 4"	●	●	●		●	●	●	●					●
8"	●	●	●		●	●	●	●					●
<b>SteelSide</b>													
Double 5"	●	●	●		●	●	●	●					●
8"	●	●	●		●	●	●	●					●
<b>Driftwood</b>													
Double 5"													
<b>Universal</b>													
Double 5" Dutch Lap	●	●	●		●	●	●	●					●
12" Vertical Board & Batten	●	●	●		●	●	●	●					●
<b>Fascia</b>													
4"			●										●
6", 8"	●	●	●	●	●	●	●	●	●	●	●	●	●
10"			●									●	

	736 Royal Brown	624 Sage	724 Sandstone	450 Terratone	794 Thistle	120 Venetian Red	840 Wicker	Variegated Colors				
								430 Poplar	757 Southern Pecan	432 Sycamore	433 Winter Oak	
		●			●	●	●					
	●				●	●	●					
					●	●	●					
	●				●	●	●					
					●	●	●					
					●	●	●		●	●	●	●
					●	●	●					
					●	●	●					
	●	●	●	●	●	●	●					
					●	●	●					





## ALUMINUM 24" TRIM COIL COLOR MATRIX

Siding	LoMar 0737107	PVC 0710007
<b>Certainteed/Wolverine</b>		
347 CT Autumn Yellow	●	●
342 CT Barn Red	●	●
343 CT Buckskin	●	●
345 CT/WV Cypress	●	●
355 CT/WV Desert Tan	●	●
362 CT/WV Granite Gray	●	●
354 CT/WV Heritage Cream	●	●
316 CT/WV Herringbone	●	●
327 CT/WV Ivy Green	●	●
350 CT/WV Light Maple	●	●
349 CT/WV Musket Brown	●	●
359 CT/WV Natural Clay	●	●
505 CT/WV Oxford Blue	●	●
601 CT/WV Pacific Blue	●	●
317 WV Pale Ivory	●	●
712 CT/WV Sable Brown	●	●
724 CT/WV Sandstone Beige	●	●
840 CT/WV Savannah Wicker	●	●
363 CT/WV Silver Ash	●	●
885 CT/WV Snow	0735007	●
R10 WV Soft Almond	●	●
365 CT/WV Sterling Gray	●	●
369 CT Summer Wheat	●	●
725 CT/WV Warm Sand	●	●
370 CT Woodland Mist	●	●
<b>Crane</b>		
316 C Bone		●
507 C Bone	●	
476 C Cabin Brown		●
359 C Clay	●	●
462 C Country Beige	●	●
470 C Cypress	●	●
336 C Driftwood	●	●
537 C Evergreen		●
362 C Greystone	●	●
471 C Harbor Blue	●	●
465 C Ivory	●	●
688 C Lighthouse Red		●
725 C Mocha	●	●
333 C Musket Brown	●	●
412 C Pearl	●	●
574 C Regatta Blue		●
472 C Rye	●	●
475 C Saddle	●	●
460 C Wheat	●	●
<b>James Hardie</b>		
068 JH Arctic White	●	
274 JH Autumn Tan	●	
521 JH Boothbay Blue	●	
272 JH Cobble Stone	●	
418 JH Khaki Brown	●	
279 JH Light Mist	●	
275 JH Monterey Taupe	●	
271 JH Navajo Beige	●	
270 JH Sail Cloth	●	
277 JH Sandstone Beige	●	
276 JH Timber Bark	●	

## COMPETITOR BRANDS

Siding (continued)	LoMar 0737107	PVC 0710007
<b>Mastic</b>		
004 MT Almond	●	●
724 MT Cameo	●	●
479 MT Classic Cream	●	●
001 MT Desert Sand	●	●
333 MT Musket Brown	●	●
359 MT Pebblestone	●	●
R28 MT Sage	●	●
618 MT Silver Gray	●	●
336 MT Victorian Gray	●	●
<b>Royal</b>		
R10 RC Almond	●	●
R28 RC Aspen	●	●
R11 RC Beige	●	●
R12 RC Blue Gray	●	●
R13 RC Clay	●	●
095 RC Charcoal		●
R25 RC Driftwood	●	●
R14 RC Gray	●	●
R27 RC Hickory	●	●
412 RC Linen	●	●
R68 RC Mountain Blue	●	●
R66 RC Pebble Clay	●	●
R65 RC Sage	●	●
001 RC Sand	●	●
618 RC Sterling	●	●
R67 RC Victorian Gray	●	●
R26 RC Vintage Cream	●	●
R23 RC Wicker	●	●

Windows	LoMar 0737107
<b>Andersen</b>	
A03 AN Canvas/AW White	●
A05 AN Cocoa Bean/AW White	●
A07 AN Sandtone/AW White	●
A06 AN Terratone/AW White	●
A02 AN White/AW White	●
<b>Marvin</b>	
194 MV Bahama Brown	●
046 MV Hampton Sage	●
080 MV Medium Bronze	●
196 MV Pebble Gray	●
195 MV Stone White	●

## GUTTER COIL COLOR MATRIX

Gutter Coil		004 Almond	007 Antique Ivory	048 Black	064 Bronze	418 Brownstone	088 Canyon Clay	121 Classic Brown	151 Dover Gray	258 Grecian Green	449 Linen	372 London Brown	333 Musket Brown	R60 Norwood	307 Pebble	736 Royal Brown
.027 x 11.75	0200015															
.027 x 11.875	0200020															
.027 x 11.875	0220012	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
.032 x 11.75	0200035															
.032 x 11.875	0200040															
.032 x 11.875	0220022	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

624 Sage	725 Sandalwood	724 Sandstone	450 Terratone	794 Thistle	120 Venetian Red	906 White – Hi-Gloss	905 White – Lo-Gloss	840 Wicker
						●	●	
●	●	●	●	●	●			●
						●	●	
●	●	●	●	●	●	●	●	●

**GENTEK VINYL SIDING AND SOFFIT**

Produced to precise tolerances using formulated compounds specifically designed for the plastic building products industry according to ASTM D4216, meeting or exceeding the following:

<u>Property</u>	<u>ASTM Test</u>	<u>Results</u>
<i>Tensile Strength (psi)</i>	<i>D-638</i>	<i>6,700</i>
<i>Modulus of Elasticity (psi)</i>	<i>D-638</i>	<i>410,000</i>
<i>Izod Impact (70°F)</i>	<i>D-256</i>	<i>3.6 (ft-lb/in of notch)</i>
<i>Izod Impact (32°F)</i>	<i>D-256</i>	<i>2.0 (ft-lb/in of notch)</i>
<i>Flexural Strength (psi)</i>	<i>D-790</i>	<i>14,000</i>
<i>Coefficient of Linear Expansion</i>	<i>D-696</i>	<i>5.3 x 10<sup>-5</sup> (mm/mm °C) 2.9 x 10<sup>-5</sup> (in/in °F)</i>
<i>Deflection Temperature Under Load 264 psi (°C)</i>	<i>D-648</i>	<i>73</i>

**PRODUCT PHYSICALS**

All siding products, soffit panels and accessories are made with solid color throughout. The siding products and accessories meet or exceed the ASTM Specification for Rigid Poly Vinyl Chloride (PVC) Siding D3679. All soffit products and associated accessories meet or exceed the ASTM Specification for Rigid (Unplasticized) Poly Vinyl Chloride (PVC) Soffit D4477.

The siding and soffit compound meets Class 2 requirements and conforms to weathering performances as described in ASTM 3679.

Color: Spectrophotometer controlled  
Gloss: Gardner gloss meter controlled  
Lock: Dimensionally controlled

All products meet or exceed ASTM 3679 thickness (nominal) requirements:

<i>Sequoia Select EnFusion</i>	<i>0.046"</i>
<i>Sequoia Select</i>	<i>0.046"</i>
<i>Sequoia Select Variegated</i> <i>(except Board &amp; Batten: 0.050")</i>	<i>0.046"</i>
<i>Sequoia Select Extended</i>	<i>0.046"</i>
<i>Sequoia Select Board &amp; Batten</i>	<i>0.050"</i>
<i>Berkshire Beaded</i>	<i>0.046"</i>
<i>Centennial Beaded</i>	<i>0.046"</i>
<i>Signature Supreme</i>	<i>0.044"</i>
<i>Concord (including Advantage III)</i>	<i>0.042"</i>
<i>Aurora</i>	<i>0.040"</i>
<i>Sequoia Select Ultra-Premium Soffit</i>	<i>0.044"</i>
<i>Oxford Premium Soffit</i>	<i>0.042"</i>
<i>Beaded Premium Soffit</i>	<i>0.042"</i>
<i>Fairweather Soffit</i>	<i>0.040"</i>

**WARRANTY**

All Gentek vinyl siding brands carry a Lifetime Limited Warranty including fade and hail protection. *Warranty is transferable if the home is sold. See printed warranty for complete details.*

**SOFFIT VENTILATION AREA**

Gentek soffit panels are designed to allow air circulation into the attic areas to aid in the reduction of excessive heat buildup and water vapor condensation. The net free open area (NFOA) per lineal foot of soffit is as follows:

<i>12" Sequoia Select Hidden Vented</i>	<i>10 sq in</i>
<i>10" Oxford Fully Vented</i>	<i>5.3 sq in</i>
<i>8" Beaded Vented</i>	<i>2.4 sq in</i>
<i>12" Fairweather Center Vented</i>	<i>2.3 sq in</i>
<i>12" Fairweather Fully Vented</i>	<i>7.1 sq in</i>

**FIRE RESISTANCE RATINGS**

Gentek vinyl siding products meet or exceed all building code requirements throughout the United States and Canada. In addition to meeting these code requirements, Gentek vinyl sidings have been fire rated by Underwriters Laboratories (UL) to be used in one-hour rated designed walls U026 and U032 and a two-hour rated wall, U301. UL inspects the manufacture of the vinyl products quarterly to certify that Gentek vinyl products are manufactured consistently. The vinyl products have been tested as follows:

<u>Property</u>	<u>ASTM Test</u>	<u>Results</u>
<i>Average Burn Distance</i>	<i>D-635</i>	<i>20mm</i>
<i>Average Burn Time</i>	<i>D-635</i>	<i>&lt;5 seconds</i>
<i>Flash Ignition Temperature</i>	<i>D-1929</i>	<i>752°F</i>
<i>Self Ignition Temperature</i>	<i>D-1929</i>	<i>860°F</i>
<i>Flame Spread Index</i>	<i>E-84</i>	<i>15</i>
<i>Smoke Developed Index</i>	<i>E-84</i>	<i>&lt;400</i>
<i>Fire Resistance</i>	<i>E-119</i>	<i>1-hour rated* 2-hour rated*</i>

\*See UL Fire Resistance Directory Control No. 1N60. E-119 is equivalent to UL-263 and E-84 is equivalent to UL-723.

**Important fire safety information for the building trades, specifiers, professionals and do-it-yourself installers:**

When rigid vinyl siding is exposed to significant heat or flame, the vinyl will soften, sag, melt, or burn and may thereby expose the material underneath. Care must be exercised when selecting underlay materials because many underlays are made from organics that are combustible. You should ascertain the fire properties of any underlay prior to installation. All building materials should be installed in accordance with local, state and federal building codes and fire regulations.

**WINDLOAD PROPERTIES**

All Gentek siding products are designed to withstand a minimum of 100 mph windloads and are suitable for most areas. The products can be used in areas with higher windloads, but installation procedures, choice of product and building code jurisdiction are important factors to be considered. The windspeed rating (in mph) is calculated using VSI's windspeed calculation guidelines. Additional information is available if required.

**BUILDING CODES**

Gentek vinyl products meet or exceed the following building code specifications:

*ICC-ESR – 1133*  
*CCMC – 06541-L*  
*New York City MEA 132-94-M*  
*FHA/HUD Minimum Property Standards*

### GENTEK SHAKES AND SCALLOPS

Gentek shakes and scallops are produced from a modified (ASTM 5630) outdoor polypropylene copolymer, also known as a reinforced thermoplastic polyolefin (TPO). Produced to precise tolerances using formulated compounds specifically designed for exterior applications, meeting or exceeding the following:

<u>Property</u>	<u>ASTM Test</u>	<u>Results</u>
<i>Tensile Strength @ Yield (psi)</i>	<i>D-638</i>	<i>3,000</i>
<i>Izod Impact (23°C)</i>	<i>D-256</i>	<i>2.5 (ft-lb/in of notch)</i>
<i>Flexural Modulus (psi)</i>	<i>D-790</i>	<i>200,000</i>
<i>Gardner Impact (23°C)</i>	<i>D-5420</i>	<i>180 (in-lb)</i>
<i>Windload</i>	<i>5206</i>	<i>205 mph Traditional Shake 267 mph Scallop 214 mph Cape Cod Shingle 217 mph Hand-Split Shake</i>

### PRODUCT PHYSICALS

The material has a solid color throughout and is UV stabilized. Shakes and scallops are continually tested for weatherability in both light and darker colors.

Material thickness:

Traditional Shake: 0.085"

Scallop: 0.085"

Cape Cod Shingle: 0.075"

Hand-Split Shake: 0.100"

Color: Spectrophotometer controlled

Traditional Shake

7" panel (single course) exposure by 81" exposure

26 panels per 100 sq ft coverage

Panel weight of 3.07 lb

Natural cedar texture

Scallop

6-1/4" panel (single course) exposure by 76" exposure

30 panels per 100 sq ft of coverage

Panel weight of 2.3 lb

Natural cedar texture

Cape Cod Shingle

10" panel (double course) exposure by 65" exposure

22 panels per 100 sq ft coverage

Panel weight of 3.2 lb

Natural cedar texture

Hand-Split Shake

9" panel (single course) exposure by 76.5" exposure

22 panels per 100 sq ft of coverage

Panel weight of 4.1 lb

Deep cedargrain texture

Staggered bottom edge

### WARRANTY

Lifetime Limited Transferable Warranty. *See printed warranty for complete details.*

### FIRE SAFETY

When polypropylene material is exposed to considerable heat or flame the polypropylene will soften, melt or burn and may possibly expose the material underneath. Care needs to be taken when selecting underlayment materials because many are made from organic materials that are combustible. Fire properties of underlayment materials must be established prior to their installation. All burning materials should be installed in accordance with local, state (provincial) and federal fire regulations and building codes.

### INSTALLATION

Complete installation instructions for shakes and scallops are available. Please review prior to installation.

## GENTEK ALUMINUM SIDING AND SOFFIT

### ALUMINUM METAL PROPERTIES

Alloy or Equivalent	3000 series
Specific Gravity	2.72
Minimum Ultimate Strength (KSI)	25
Minimum Yield (KSI)	22
Minimum Elongation (%)	1
Modulus of Elasticity (KSI)	10,000
Coefficient of Thermal Expansion (in/in °F)	0.0000131
Melting Range (°F)	1175-1210
Thermal Conductivity at 77°F (btu-in/ft <sup>2</sup> -hr=°F)	1190

### COATING PROPERTIES

Gentek aluminum siding products are manufactured with AA3000 series alloy or equivalent. Both sides of the aluminum sheet are cleaned with a specially formulated cleaner, water rinsed and then coated with an environmentally safe chemical pretreatment to enhance corrosion protection and coating adhesion.

The pretreated aluminum is coated with a corrosion-resistant polymer. This corrosion-resistant polymer (i.e., primer) can then be top coated with the following polymeric systems:

**Polyester (Poly) Topcoat:** This thermoset polymer resin is cured at 450°F forming a hard, flexible, mar resistant and weatherable coating. The coating thickness is 0.8 mil.

**Plastisol (PVC) Topcoat:** This highly weatherable, flexible, chemical-resistant thermoplastic polymer is melted and fused on the aluminum metal at temperatures of 390°F. The coating is applied either with a striated pattern or smooth finish having an average film thickness of 3.0 mils.

**Fluoropolymer (PVDF):** This thermoplastic polymer has excellent chemical and fade resistance. The coating is applied at 0.9 mil. The system is cured at a minimum temperature of 475°F. This polymer system conforms to the high industry standards of Kynar 500® and Hylar 5000®. The main criteria for these standards is that the paint formulation must contain a minimum of 70% PVDF. Many fluoropolymer coatings on the market do not meet the high quality and performance standards required by Kynar 500 and Hylar 5000 specifications.

### WARRANTY

All Gentek aluminum siding brands carry a Lifetime Limited Warranty. Warranty is transferable if home is sold. See printed warranty for complete details.

### CONTACT WITH DISSIMILAR MATERIALS

Direct contact of aluminum products with certain dissimilar materials, or contact with water runoff from dissimilar materials, is likely to result in corrosion. Accordingly, care should be taken during installation to avoid such contact of aluminum with dissimilar materials, including: dissimilar metals (copper, zinc, steel, etc.), concrete, stucco, asbestos siding, pressure treated/pretreated lumber, masonry, corrosive non-metallic materials, and roofing materials or roofing systems containing metallic granules or strips.

### PRODUCT PHYSICALS

Product	Coating Type	Thickness
Cedarwood	PVDF	0.024
Woodgrain Series 2000	Poly	0.019
Deluxe 4"	Poly	0.019
Deluxe 8"	Poly	0.024
Hi-Tensile Soffit	Poly	0.016
PVC Supreme Soffit	PVC	0.016
ValuGuard Soffit	Poly	0.014
Deluxe Fascia	Poly	0.024
ValuGuard Fascia	Poly	0.019
HD Trim Coil	Poly	0.024
Trim Coil	Poly	0.019
Trim Coil	PVC	0.019

### SOFFIT VENTILATION AREA

Gentek soffit panels are designed to allow air circulation into the attic areas to aid in the reduction of excessive heat buildup and water vapor condensation. The net free open area (NFOA) per lineal foot of soffit are as follows:

Profile	Vent	NFOA (in <sup>2</sup> /foot)
16" 4 Panel	Center/Vent	7.8
	Full Vent	15.5
12" 3 Panel	Center/Vent	3.9
	Full Vent	11.6

### BUILDING CODES

Gentek aluminum products meet or exceed the following building code specifications:

ICC-ES Legacy – Report #97-64  
 AAMA 1402-86  
 FHA/HUD Minimum Property Standards

## GENTEK GALVANIZED STEEL SIDING

### GALVANIZED METAL PROPERTIES

Galvanized Steel or Equivalent	G90
Specific Gravity	7.8
Minimum Ultimate Strength (KSI)	45-55
Minimum Yield (KSI)	40-50
Minimum Elongation (%)	25-35
Modulus of Elasticity (KSI)	29,500
Coefficient of Thermal Expansion (in/in °F)	0.000006
Melting Range (°F) Steel	>2700
Melting Range (°F) Zinc	786
Thermal Conductivity at 77°F (btu-in/ft <sup>2</sup> -hr-°F)	555

### COATING PROPERTIES

Gentek galvanized steel siding products are manufactured with G90 or equivalent. Both sides of the steel sheet are cleaned with a specially formulated acid cleaner, water rinsed and then coated with an environmentally safe chemical pretreatment to enhance corrosion protection and coating adhesion.

The pretreated galvanized surface is coated with a thermoset corrosion-resistant polymer. This corrosion-resistant polymer is topcoated with the following polymeric systems:

**Plastisol (PVC) Topcoat:** This highly weatherable, flexible, chemical-resistant thermoplastic polymer is melted and fused at temperatures of >390°F. The coating is applied with a striated pattern or smooth finish having an average film thickness of 3.0 mils.

**Fluoropolymer (PVDF):** This thermoplastic polymer has excellent chemical and fade resistance. The coating thickness is 0.9 mil. The system is cured at a minimum temperature of 475°F. This polymer system conforms to the high industry standards of Kynar 500® and Hylar 5000®. The main criteria for these standards is that the paint formulation must contain a minimum of 70% PVDF. Many fluoropolymer coatings on the market do not meet the high quality and performance standards required by Kynar 500 and Hylar 5000 specifications.

### WARRANTY

All Gentek steel siding brands carry a Lifetime Limited Warranty. Warranty is transferable if home is sold. See printed warranty for complete details.

### CONTACT WITH DISSIMILAR MATERIALS

Direct contact of steel products with certain dissimilar materials, or contact with water runoff from dissimilar materials, is likely to result in corrosion. Accordingly, care should be taken during installation to avoid such contact of steel with dissimilar materials, including: dissimilar metals (copper, zinc, steel, etc.), concrete, stucco, asbestos siding, pressure treated/pretreated lumber, masonry, corrosive non-metallic materials, and roofing materials or roofing systems containing metallic granules or strips.

## PRODUCT PHYSICALS

Product	Coating Type	Thickness*
SteelTek	PVC	0.017
SteelSide	PVC	0.017
Driftwood	PVC	0.017
Universal	PVC	0.017

\*29 Gauge

### BUILDING CODES

Gentek steel products meet or exceed the following building code specifications:

ICC-ES Legacy – Report #97-64  
 AIAA 1406-86  
 FHA/HUD Minimum Property Standards

[www.gentekinc.com](http://www.gentekinc.com)



P.O. Box 110 • Akron, Ohio 44309  
[www.gentekinc.com](http://www.gentekinc.com)

*Make us a part of your home.*



Due to product changes, improvements and other factors, Gentek reserves the right to change or delete information contained herein without prior notice. USGBC and related logo is a trademark owned by the U.S. Green Building Council and is used by permission.

Effective Date: 4/1/10

